

AUTOMATIC LEVEL REGULATION

2 types of « WATER DROP » shaped float level switches that benefit from the long experience of « ATMI »



AQUA-ECO

ECOLOGICAL OMNIDIRECTIONAL FLOAT LEVEL SWITCHES

- Alarm – Filling – Emptying functions
- «Lack of water» security function
- High and low level regulation
- Direct connection to pumps
- Equipment of pumping stations

SIMPLE USE – ATTRACTIVE PRICE
100% FRENCH MANUFACTURING
Quality Components



AQUA-PLUS

AQUA-ECO - Green colour

- Operation mode = Omnidirectional
- Microswitch = 250 VAC/VDC-50/60 Hz
16A resistive / 6A inductive
- Connection = V (Emptying) - R (Filling)
- Protection index = IP 68
- Maximum pressure = 3,5 bars
- Maximum temperature = 70°C
- Housing material = Polypropylene
- Electrical cable = PVC 3x0,75 mm²
- 260g "clip-type" ballast on option
(instantaneous mounting)
- Devices available with 2, 5, 10 m. of cable
- Dimensions: Height 140mm / Diameter: 70mm
- Float weight without cable: 250 g
- Total weight with 1m of 3x0,75 mm² cable
 - without ballast = 330g.
 - with 1 ballast = 590g.
 - with 2 ballasts = 850g.

AQUA PLUS – Blue colour

- Operation mode = Omnidirectional
- Microswitch = 250 VAC/VDC-50/60 Hz
20 A resistive / 8 A inductive
- Connection = V (Emptying) - R (Filling)
- Protection index = IP 68
- Maximum pressure = 3,5 bars
- Maximum temperature = 70°C
- Housing material = 1° quality copolymer polypropylene
- Electrical cable = PVC 3x1 mm²
- 1 or 2 ballasts on option: 260g "clip-type" ballast
(instantaneous mounting)
- Devices available with 5, 10, 15, 20, 25 m. of cable
- Dimensions: Height 140mm / Diameter: 70mm
- Float weight without cable: 250 g
- Total weight with 1m of 3x1 mm² cable
 - without ballast:= 340g.
 - with 1 ballast = 600g.
 - with 2 ballasts = 860g.

The use of cable holders is highly recommended for all types of float level switches

Applications Techniques Modernes Industrielles - Division AQUASYSTEMS

2, avenue des Bosquets - 78180 Montigny Le Bretonneux, France

Phone: + 33 1 61 37 35 60 - Fax: +33 1 61 37 35 69 – Website: www.atmi.fr - E-mail: sales@atmi.fr